

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy resin L1100

Print date: 05.02.2013

Product code: 103100-GHS-2012

Page 1 of 8

1. Identification of the substance/mixture and of the company/undertaking

Identification of the substance or mixture

Epoxy resin L1100

Use of the substance/mixture

epoxy resin systems

Company/undertaking identification

Company name:	R&G Faserverbundwerkstoffe GmbH	
	Composite Technology	
Street:	Im Meißel 7 - 13	
Place:	D-71111 Waldenbuch	
Post-office box:	1145	
	D-71107 Waldenbuch	
Telephone:	+49-7157-530460	Telefax: +49-7157-530470
e-mail:	info@r-g.de	
Internet:	www.r-g.de	
Responsible Department:	Management	
1.4. Emergency telephone number:	poison information centre	

2. Hazards identification

Classification

Indications of danger: Irritant, Dangerous for the environment

R phrases:

Irritating to eyes.

Irritating to skin.

May cause sensitisation by skin contact.

Toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

GHS: Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory/skin sensitization: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

Explication of special hazards for human health and environment

The residual content of epichlorohydrin complies with the APME recommendations for modified epoxy resins. < 10ppm (0,001%).

3. Composition/information on ingredients

Chemical characterization (Mixture)

Modifiziertes Epoxidharz

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy resin L1100

Print date: 05.02.2013

Product code: 103100-GHS-2012

Page 2 of 8

Hazardous components

EC No	CAS No	Chemical name	Quantity
		Classification	
		GHS classification	
500-033-5	25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	> 50%
		Xi - Irritant, N - Dangerous for the environment R36/38-43-51-53	
		Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411	
271-846-8	68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	< 10%
		Xi - Irritant R38-43	
		Skin Irrit. 2, Skin Sens. 1; H315 H317	

Full text of R and H phrases: see Section 16.

4. First aid measures

General information

Change contaminated clothing.

After inhalation

Following inhalation: Move victim to fresh air. Consult physician. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with soap and plenty of water. If skin becomes irritated, seek medical treatment.

After contact with eyes

After contact with eye rinse immediately with lot of water at least 5 minutes with open eyelid. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink large quantities of water. Consult physician.

5. Fire-fighting measures

Suitable extinguishing media

Carbon dioxide (CO₂).
Extinguishing powder.
Water fog.
Fight major fires with a water spray jet or alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

High power water jet.

Special exposure hazards arising from substance or mixture itself, combustion products, resulting gases

In case of fire may form: Carbon monoxide. Under certain conditions traces of toxic substances cannot be ruled out, e.g.: Chlorhydric gas (HCl).

Special protective equipment for fire-fighters

Wear a protective full body suit. Wear breathing apparatus with own air supply.

Additional information

Contaminated fire-fighting water must be collected separately. Contaminated fire-fighting water must not get into the sewerage network. Fire residue and contaminated firefighting water must be disposed of in accordance with government regulations.

6. Accidental release measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy resin L1100

Print date: 05.02.2013

Product code: 103100-GHS-2012

Page 3 of 8

Personal precautions

Wear personal protection equipment. Keep unprotected persons at a safe distance.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. Do not allow to enter the soil or subsoil.

Methods for cleaning up/taking up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Dispose of contaminated material as § 13 waste.

7. Handling and storage

Handling

Advice on safe handling

Provide for sufficient ventilation and punctiform suction at critical points.

Advice on protection against fire and explosion

No special measures are necessary.

Storage

Requirements for storage rooms and vessels

Employ reliable measures to prevent the product from entering the soil.

Further information on storage conditions

Keep in well sealed receptacles at a cool, dry location.

Storageclass (D): 10

8. Exposure controls/personal protection

Exposure limit values

8.2. Exposure controls

Protective and hygiene measures

Take off immediately all contaminated clothing Avoid contact with skin and eyes. Wash hands before breaks and after work.

Respiratory protection

Not necessary when the room is well ventilated.

Hand protection

Wear protective gloves. (EN 374)
Material: NBR (Nitrile rubber). Butyl rubber.
Breakthrough time: See information supplied by the manufacturer.

Eye protection

Tightly sealed safety glasses. (EN 166)

Skin protection

Wear protective clothing. (EN 340)

9. Physical and chemical properties

General information

Physical state:	liquid
Colour:	light yellow
Odour:	weak, characteristic

Important health, safety and environmental information

Test method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy resin L1100

Print date: 05.02.2013

Product code: 103100-GHS-2012

Page 4 of 8

Changes in the physical state

Boiling point:	> 200 °C	DIN 53171
Flash point:	> 100 °C	ISO 2719
Vapour pressure: (at 20 °C)	< 0,1 hPa	
Density (at 20 °C):	1,12 - 1,14 g/cm ³	DIN 53217
Water solubility:	not miscible / slightly soluble	
Viscosity / dynamic: (at 25 °C)	1.200 - 1.800 mPa·s	ISO 9371

10. Stability and reactivity

10.4. Conditions to avoid

no decomposition when stored and handled properly

10.6. Hazardous decomposition products

Violent reaction with: alkalis and numerous organic substance categories like alcohols and amines
polymerisation under the action of heat
Thermal decomposition can lead to the escape of irritating gases and vapors.

11. Toxicological information

Specific effects in experiment on an animal

25068-38-6 Bisphenol A-epichlorohydrin resin mw<= 700:
oral: 11.400 mg/kg (rat) LD50
dermal: >2.000 mg/kg (rat) LD50
68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:
oral: 17.100 mg/kg (rat) LD50

Irritation and corrosivity

Irritation to skin, eyes, and mucous membranes.

Sensitising effects

Contact may cause skin sensitisation.

12. Ecological information

Ecotoxicity

Bisphenol A-epichlorohydrin resin mw<= 700
Oncorhynchus mykiss: LC50 (96h) 1,5-7,7 mg/l
Daphnia magna: EC50 (24h) 1,1-3,6 mg/l
Green algae: EC50 (96h) 220 mg/l

12.2. Persistence and degradability

Product is biodegradable with difficulty.

Further information

Do not let the product enter the groundwater, open water, or the sewerage system.

13. Disposal considerations

Advice on disposal

Dispose of waste according to applicable local, state, and federal regulations. e.g. transfer to a suitable incineration plant
Waste key numbers are assigned according to the European Waste Catalogue (EWC) depending on the sector and process type.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy resin L1100

Print date: 05.02.2013

Product code: 103100-GHS-2012

Page 5 of 8

Contaminated packaging

Dispose of waste according to applicable local, state, and federal regulations.

14. Transport information

Land transport (ADR/RID)

14.1. UN number: 3082
ADR/RID class: 9
Classification code: M6
Warning plate
Hazard No: 90
Hazard label: 9



ADR/RID packing group: III
Limited quantity: LQ7
Tunnel restriction code: E

Description of the goods


ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxidderivate)

Other applicable information (land transport)

Special provisions: 274 335 601
E1
: 3

Marine transport (IMDG)

14.1. UN number: 3082
IMDG code: 9
Marine pollutant: •
Hazard label: 9



IMDG packing group: III
EmS: F-A, S-F
Limited quantity: 5 L

Description of the goods

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(Epoxidderivate)

Other applicable information (marine transport)

Special provisions: 274, 909, 944
E1

Air transport (ICAO)

UN/ID number: 3082
ICAO/IATA-DGR: 9
Hazard label: 9

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy resin L1100

Print date: 05.02.2013

Product code: 103100-GHS-2012

Page 6 of 8



ICAO packing group: III
Limited quantity Passenger: 30 kg G
IATA-packing instructions - Passenger: 914
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 914
IATA-max. quantity - Cargo: 450 L

Description of the goods

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxidderivate)

Other applicable information (air transport)

E1
: Y914
Special provisions: A97 A158

15. Regulatory information

Labelling

Danger symbols: Xi - Irritant; N - Dangerous for the environment



Xi - Irritant



N - Dangerous for the environment

Hazardous components which must be listed on the label

Bisphenol A-epichlorohydrin resin $m_w \leq 700$
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

R phrases

36 Irritating to eyes.
38 Irritating to skin.
43 May cause sensitisation by skin contact.
51 Toxic to aquatic organisms.
53 May cause long-term adverse effects in the aquatic environment.

S phrases

24 Avoid contact with skin.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
37 Wear suitable gloves.
60 This material and its container must be disposed of as hazardous waste.
61 Avoid release to the environment. Refer to special instructions / Safety data sheets.

Special labelling of certain mixtures

Contains epoxy constituents. See information supplied by the manufacturer.

Additional advice on labelling

The product is classified and labelled under the EC Directives/hazardous substances laws (GefStoffV).

GHS labelling

Signal word: Warning
Pictograms: exclamation mark; environment

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy resin L1100

Print date: 05.02.2013

Product code: 103100-GHS-2012

Page 7 of 8



Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P321	Specific treatment (see ... on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P501	Dispose of contents/container to

National regulatory information

Water contaminating class (D): 2 - water contaminating

Additional information

APME document: "Epoxidharze und Härter (Toxikologie, Arbeitssicherheit, Umwelt)" ("Epoxy resins and hardeners (toxicology, work safety, environment)")

16. Other information

Full text of R phrases referred to under Sections 2 and 3

36	Irritating to eyes.
36/38	Irritating to eyes and skin.
38	Irritating to skin.
43	May cause sensitisation by skin contact.
51	Toxic to aquatic organisms.
53	May cause long-term adverse effects in the aquatic environment.

Full text of H statements referred to under Sections 2 and 3

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Further Information

All information, recommendations, and advice on the part of R&G Faserverbundwerkstoffe GmbH are published to the best of our knowledge and belief. They are noncommittal and contain neither explicit nor tacit assurance or warranty of particular properties. The values specified for properties are typical figures. Recommendations or advice serve to describe our products and possible applications in a

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy resin L1100

Print date: 05.02.2013

Product code: 103100-GHS-2012

Page 8 of 8

general or exemplary, but not specifically individual manner. In the course of the constant technical advancement and improvement of our products there may be changes to the characteristic values, copy, and diagrams; no specific reference is made to any such change. Owing to our products' wide and highly diverse range of potential applications far beyond any of our attempts to analyse, the customer alone is responsible for examining our products' suitability for the respective processes and purposes and their respective processibility. All and any protective rights and the applicable laws, terms, and conditions must be observed by the buyer or user of our products at their own responsibility. Publication is not a licence and does not intend the violation of any patents.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)