

according to Regulation (EU) No. 1907/2006

# EP gel coat white (120140-X)

Print date : 20.02.2008 Product code : 120140-X Page 1 of 6

### 1. Identification of the substance/preparation and of the company/undertaking

#### Identification of the substance or preparation

EP gel coat white (120140-X)

#### Company/undertaking identification

Company name : R&G Faserverbundwerkstoffe GmbH

Composite Technology

Place : D-71111 Waldenbuch

Telephone: +49-7157-530460 Telefax: +49-7157-530470

e-mail : info@r-g.de Internet : www.r-g.de

Inquiry office : business management Emergency telephone : poison information centre

#### 2. Hazards identification

#### Classification

Indications of danger: Irritant, Dangerous for the environment

R-phrases:

Irritating to eyes and skin.

May cause sensitization by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# Explication of special hazards for human health and environment

The residual content of epichlorohydrin complies with the APME recommendations for modified epoxy resins. < 10 ppm (0,001%)

# 3. Composition/information on ingredients

# Chemical characterization ( preparation )

Modifiziertes Epoxidharz

#### Hazardous components

EC-No.	CAS-No.	Chemical name	Quantity	Classification
240-260-4	16096-31-4	1,6-Hexandioldiglycidylether	> 50%	Xi R36-38-43-52-53
500-033-5		epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	< 25%	Xi, N R36/38-43-51-53
500-006-8		epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-F-(epichlorhydrin)	< 25%	Xi, N R36/38-43-51-53

Full text of each relevant R phrase can be found in heading 16.

# 4. First aid measures

#### **General information**

Change contaminated clothing.

#### After inhalation

Following inhalation: Move victim to fresh air. Consult physician. If victim is at risk of losing consciousness, position and transport on their side.

#### After contact with skin

After contact with skin, wash immediately with soap and plenty of water. If skin becomes irritated, seek medical treatment.



according to Regulation (EU) No. 1907/2006

# EP gel coat white (120140-X)

Print date : 20.02.2008 Product code : 120140-X Page 2 of 6

#### After contact with eyes

After contact with eye rinse immediately with lot of water at least 5 minutes with open eyelid. Subsequently consult an opthalmologist.

#### After ingestion

Rinse mouth immediately and drink large quantities of water. Consult physician.

# 5. Fire-fighting measures

### Suitable extinguishing media

Carbon dioxide (CO2).

Extinguishing powder.

Water fog.

Fight major fires with a water spray jet or alcohol-resistant foam.

#### Extinguishing media which must not be used for safety reasons

High power water jet.

# Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

In case of fire may form: Carbon monoxide. Under certain conditions traces of toxic substances cannot be ruled out, e.g.: Chlorhydric gas (HCI).

#### Special protective equipment for fire-fighters

Wear a protective full body suit. Wear breathing apparatus with own air supply.

#### Additional information

Contaminated fire-fighting water must be collected separately. Contaminated fire-fighting water must not get into the sewerage network. Fire residue and contaminated firefighting water must be disposed of in accordance with government regulations.

### 6. Accidental release measures

#### Personal precautions

Wear personal protection equipment. Keep unprotected persons at a safe distance.

# **Environmental precautions**

Do not empty into drains or the aquatic environment. Do not allow to enter the soil or subsoil.

#### Methods for cleaning up/taking up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Dispose of contaminated material as § 13 waste.

#### 7. Handling and storage

#### Handling

# Advice on safe handling

Provide for sufficient ventilation and punctiform suction at critical points.

#### Advice on protection against fire and explosion

No special measures are necessary.

### **Storage**

#### Requirements for storage rooms and vessels

Employ reliable measures to prevent the product from entering the soil.

### Further information on storage conditions

Keep in well sealed receptacles at a cool, dry location.

Storageclass (VCI): 10

#### 8. Exposure controls/personal protection

Test method



# **Safety Data Sheet**

according to Regulation (EU) No. 1907/2006

# EP gel coat white (120140-X)

Print date: 20.02.2008 Product code: 120140-X Page 3 of 6

### **Exposure limit values**

#### **Exposure controls**

# Protective and hygiene measures

Take off immediately all contaminated clothing Avoid contact with skin and eyes. Wash hands before breaks and after work.

#### Respiratory protection

Not necessary when the room is well ventilated.

#### Hand protection

Wear protective gloves. (EN 374)

Material: NBR (Nitrile rubber). Butyl rubber.

Breakthrough time: See information supplied by the manufacturer.

#### Eye protection

Tightly sealed safety glasses. (EN 166)

#### Skin protection

Wear protective clothing. (EN 340)

### 9. Physical and chemical properties

# **General information**

Physical state : Paste Colour : white

Odour : weak, characteristic

#### Important health, safety and environmental information

Changes in the physical state

Boiling point :  $> 200 \, ^{\circ}\text{C}$  DIN 53171 Flash point :  $> 150 \, ^{\circ}\text{C}$  ISO 2719

Vapour pressure : < 0,1 hPa

(at 20 °C)

Density (at 20 °C): 1,37-1,41 g/cm³ DIN 53217

Water solubility: not miscible / slightly soluble

Viscosity / dynamic : 100.000 mPa⋅s ISO 9371

(at 25 °C)

**Other information** 

Ignition temperature: > 300 °C DIN 51794

# 10. Stability and reactivity

# Conditions to avoid

no decomposition when stored and handled properly

# Hazardous decomposition products

Violent reaction with: alkalis and numerous organic substance categories like alcohols and amines polymerisation under the action of heat Thermal decomposition can lead to the escape of irritating gases and vapors.

# 11. Toxicological information

# Specific effects in experiment on an animal

LD/LC50: 25068-38-6 Bisphenol A-epichlorohydrin resin mw<= 700

oral: 11.400 mg/kg (rat) LD50 dermal: >2.000 mg/kg (rabbit) LD50



according to Regulation (EU) No. 1907/2006

# EP gel coat white (120140-X)

Print date : 20.02.2008 Product code : 120140-X Page 4 of 6

#### Corrosive and irritant effects

Irritation to skin, eyes, and mucous membranes.

#### Sensitising effects

Contact may cause skin sensitisation.

# 12. Ecological information

### **Ecotoxicity**

Bisphenol A-epichlorohydrin resin mw<= 700 Oncorhynchus mykiss: LC50 (96h) 1,5-7,7 mg/l Daphnia magna: EC50 (24h) 1,1-3,6 mg/l Green algae: EC50 (96h) 220 mg/l

#### Persistence and degradability

Product is biodegradable with difficulty.

#### **Further information**

Do not let the product enter the groundwater, open water, or the sewerage system.

# 13. Disposal considerations

#### Advice on disposal

Dispose of waste according to applicable local, state, and federal regulations. e.g. transfer to a suitable incineration plant Waste key numbers are assigned according to the European Waste Catalogue (EWC) depending on the sector and process type.

#### Contaminated packaging

Dispose of waste according to applicable local, state, and federal regulations.

#### 14. Transport information

# Land transport (ADR/RID)

UN number: 3082
ADR/RID class: 9
Classification code: M6
Warning plate

Hazard-no.: 90
Hazard label: 9
ADR/RID packing group: III
Limited quantity: LQ7

### **Description of the goods**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

# Remarks (land transport)

: 274 - 601 : 3 : E

#### Marine transport

 UN number :
 3082

 IMDG code :
 9

 Marine pollutant :
 yes

 Hazard label :
 9

 IMDG packing group :
 III

 EmS :
 F-A, S-F

 Limited quantity :
 5 L



according to Regulation (EU) No. 1907/2006

# EP gel coat white (120140-X)

Print date : 20.02.2008 Product code : 120140-X Page 5 of 6

#### Description of the goods

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

### Remarks (marine transport)

: 274, 909, 944

#### Air transport

UN/ID number: 3082
ICAO/IATA-DGR: 9
Hazard label: 9
ICAO packing group: III
Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger :914IATA-max. quantity - Passenger :450 LIATA-packing instructions - Cargo :914IATA-max. quantity - Cargo :450 L

# **Description of the goods**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

#### Remarks (air transport)

: Y914 : A97

## 15. Regulatory information

### Labelling

Danger symbols : Xi - Irritant; N - Dangerous for the environment

#### Hazardous component(s) to be indicated on label

Bisphenol A-epichlorohydrin resin mw<= 700 Bisphenol F-epichlorohydrin resin mw<= 700 1,6-Hexandioldiglycidylether

R phrases

36/38 Irritating to eyes and skin.

43 May cause sensitization by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S phrases

After contact with skin, wash immediately with plenty of Wasser und Seife.
This material and its container must be disposed of as hazardous waste.

Avoid release to the environment. Refer to special instructions / Safety data sheets.

37/39 Wear suitable gloves and eye/face protection.

#### Special labelling for certain preparations

Contains epoxy constituents. See information supplied by the manufacturer.

# Additional advice on labelling

The product is classified and labelled under the EC Directives/hazardous substances laws (GefStoffV).

# **National regulatory information**

Water contaminating class : 2 - water contaminating

# **Additional information**

APME document: "Epoxidharze und Härter (Toxikologie, Arbeitssicherheit, Umwelt)" ("Epoxy resins and hardeners (toxicology, work safety, environment)")

# 16. Other information

### Full text of R-phrases referred to under sections 2 and 3

36 Irritating to eyes.



according to Regulation (EU) No. 1907/2006

# EP gel coat white (120140-X)

Print date : 20.02.2008 Product code : 120140-X Page 6 of 6

36/38 Irritating to eyes and ski
----------------------------------

38 Irritating to skin.

43 May cause sensitization by skin contact.

51 Toxic to aquatic organisms.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

52 Harmful to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

#### **Further Information**

All information, recommendations, and advice on the part of R&G Faserverbundwerkstoffe GmbH are published to the best of our knowledge and belief. They are noncommittal and contain neither explicit nor tacit assurance or warranty of particular properties. The values specified for properties are typical figures. Recommendations or advice serve to describe our products and possible applications in a general or exemplary, but not specifically individual manner. In the course of the constant technical advancement and improvement of our products there may be changes to the characteristic values, copy, and diagrams; no specific reference is made to any such change. Owing to our products' wide and highly diverse range of potential applications far beyond any of our attempts to analyse, the customer alone is responsible for examining our products' suitability for the respective processes and purposes and their respective processibility. All and any protective rights and the applicable laws, terms, and conditions must be observed by the buyer or user of our products at their own responsibility. Publication is not a licence and does not intend the violation of any patents.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)