Printing date 19.12.2008 Revision: 19.12.2008

1 Identification of the substance/preparation and of the company/undertaking

- · Product details
- · Trade name: prestolith easy light filler
- · Article number: 601457, 793899, 483527, 482650
- · Application of the substance / the preparation Knife filler/ Surfacer
- · Manufacturer/Supplier:

MOTIP DUPLI GmbH

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49/6266/75-0

sicherheitsdatenblatt@dupli-color.de

- · Further information obtainable from: Abteilung Produktsicherheit
- · Information in case of emergency:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Do 08:00 - 16:00 Uhr, Fr 08:00 - 12:30 Uhr)

2 Hazards identification

· Hazard description:



Xn Harmful

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 20 Harmful by inhalation.

R 36/38 Irritating to eyes and skin.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- · Chemical characterization
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 100-42-5 styrene EINECS: 202-851-5

Xn, Xi; R 10-20-36/38

10-25%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 2)

Printing date 19.12.2008 Revision: 19.12.2008

Trade name: prestolith easy light filler

(Contd. of page 1)

· After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

5 Fire-fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

- · Handling:
- · Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

WEL () Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 3)

Printing date 19.12.2008 Revision: 19.12.2008

Trade name: prestolith easy light filler

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical	l and cl	hemical	properties
------------	----------	---------	------------

General Information			
Form:	Fluid		
Colour:	According to product specification		
Odour:	Characteristic		
Change in condition			
Melting point/Melting rang	e: Undetermined.		
Boiling point/Boiling range	: 145°C		
Flash point:	31°C		
Self-igniting:	Product is not selfigniting.		
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor		
	mixtures are possible.		
Explosion limits:			
Lower:	1.2 Vol %		
Upper:	8.9 Vol %		
Vapour pressure at 20°C:	6 hPa		
Density at 20°C:	0.85 g/cm^3		
Solubility in / Miscibility with			
water:	Not miscible or difficult to mix.		
VOC-EU	19.6 %		
	167.9 g/l / 1.40 lb/gl		
VOC-(EU)	167.9 g/l		

(Contd. of page 2)

Printing date 19.12.2008 Revision: 19.12.2008

Trade name: prestolith easy light filler

(Contd. of page 3)

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · LD/LC50 values relevant for classification:

100-42-5 styrene

 Oral
 LD50
 5000 mg/kg (rat)

 Inhalative
 LC50/4 h
 24 mg/l (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Harmful

Irritant

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

12 Ecological information

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 04 09 waste adhesives and sealants containing organic solvents or other dangerous substances

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 (F1) Flammable liquids.

· Danger code (Kemler):

(Contd. on page 5)

Printing date 19.12.2008 Revision: 19.12.2008

Trade name: prestolith easy light filler

(Contd. of page 4)

· UN-Number: 3269 · Packaging group: III · Hazard label 3

· Description of goods: 3269 POLYESTER RESIN KIT

· Limited quantities (LQ) LQ7

· Maritime transport IMDG:



· IMDG Class: 3
· UN Number: 3269
· Label 3
· Packaging group: III
· EMS Number: F-E,S-D
· Marine pollutant: No

· Proper shipping name: POLYESTER RESIN KIT

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3
· UN/ID Number: 3269
· Label 3
· Packaging group: III

· Proper shipping name: POLYESTER RESIN KIT

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xn Harmful

· Hazard-determining components of labelling:

styrene

· Risk phrases:

10 Flammable.

20 Harmful by inhalation.

36/38 Irritating to eyes and skin.

- · Safety phrases:
- 2 Keep out of the reach of children.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 25 Avoid contact with eyes.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 56 Dispose of this material and its container to hazardous or special waste collection point.

(Contd. on page 6)

Printing date 19.12.2008 Revision: 19.12.2008

Trade name: prestolith easy light filler

(Contd. of page 5)

- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant R-phrases
- 10 Flammable.
- 20 Harmful by inhalation.

36/38 Irritating to eyes and skin.

- · Department issuing MSDS: Safety Dept.
- · Contact: Anwendungstechnik
- * Data compared to the previous version altered.

CP